




Features

- IEC/EN 60950-1
- EMC EN 55022/FCC Part 15
- Low Leakage Current
- CE / LVD / RoHS / REACH
- 5 Year Warranty
- Longlife Capacitors 105°C

CE RoHS

Specification						
Output	Model:	TSC-060-09	TSC-060-12	TSC-060-15	TSC-060-24	TSC-060-48
	DC Voltage:	9Vdc	12Vdc	15Vdc	24Vdc	48Vdc
	DC Adjustable Range:	± 5%	± 5%	± 5%	± 5%	± 5%
	Rated Current:	6.67A	5A	4A	2.5A	1.25A
	Current Range:	0 - 6.67A	0 - 5A	0 - 4A	0 - 2.5A	0 - 1.25A
	Rated Power:	60W	60W	60W	60W	60W
	Ripple & Noise:	90mVp-p	120mVp-p	200mVp-p	250mVp-p	480mVp-p
	Voltage Tolerance:	± 5%	± 5%	± 5%	± 5%	± 5%
	Line Regulation:	± 3%	± 3%	± 3%	± 3%	± 3%
	Load Regulation:	± 5%	± 5%	± 5%	± 5%	± 5%
Setup, Hold Up Time:	3 Seconds Max./40mS Max./5mS Max. at 100Vac Input and Output at Max Load					
Input:	Input Voltage:	100 - 240Vac 50/60Hz				
	Input Current:	0.8A Max.				
	Inrush Current:	80A at 240Vac 50Hz, Full Load				
	Leakage Current:	0.75mA Max. 240Vac Input				
Protection	Withstand Voltage:	I/P - O/P: 1.5kVac I/P - FG: 0.5kVac O/P - FG: 0.5kVac				
	Isolation Resistance:	I/P - O/P, I/P - FG, O/P - FG: ≥100M Ohm / 500Vdc				
	Short Circuit (SCP):	Protection to Zero Voltage				
	Over Voltage (OVP):	≤ Vout × 150%				
	Over Current (OCP):	110% - 180%				
Temp / Humidity	Working Temp.:	-20°C to +60°C				
	Storage Temp.:	-40°C to +70°C				
	Working Humidity:	5% to 90% RH Non-Condensing				
Certificates	Certificates:	CE / LVD / RoHS / REACH				
	Safety Standards:	IEC / EN60950-1				
	Warranty:	5 Years (Longlife Capacitors +105°C, 4 - 10k/h)				
	MTBF:	100K Hours Min at Full Load +25°C				
EMI Emission	Radiation:	EN55022 / FCC Part 15				
	Harmonic Current:	EN61000-3-2				
	Voltage & Flicker:	EN61000-3-3				
EMS Immunity	ESD:	EN61000-4-2				
	Radiated:	EN61000-4-3				
	EFT / Burst Immunity:	EN61000-4-4				
	Surge Immunity:	EN61000-4-5				
	RF Immunity:	EN61000-4-6				
	Voltage Interruptions:	EN61000-4-11				

Derating Curve



Dimension, Weight, Packaging		
Measurements	Dimension:	160 x 99 x 37mm (L x W x H)
	Weight:	450g
	Packaging:	20pcs/ctn. 34.5 x 24.5 x 22.5cm

Dimensions: (mm)

